

# REVO ULTRA 4K Fixed Bullet Network Camera

RUCB28-4X



## Key Features



## Optics

- True 4K (8 Megapixel) Resolution with Day/night functionality
- Smart IR , up to 98ft (30M) IR distance
- Optical glass window with higher light transmittance
- IR anti-reflection window to increase the infrared transmittance
- Built-in Microphone

## Compression

- Ultra 265, H.265, H.264, MJPEG
- ROI (Region of Interest)

## Network

- ONVIF Compliant

## Structure

- Wide temperature range: -22°F to 140°F (30°C to 60°C)
- Wide voltage range of  $\pm 25\%$
- IP67

## Specifications

RUCB28-4X					
Camera					
Sensor	1/3", 8.0 megapixel, progressive scan, CMOS				
Lens	2.8mm@F2.0				
DORI Distance	Lens	Detect(m)	Observe(m)	Recognize(m)	Identify(m)
	2.8mm	63	25.2	12.6	6.3
Angle of View (H)	112.9°				
Angle of View (V)	59.1°				
Angle of View (D)	121.2°				
Adjustment angle	Pan: 0°~360°		Tilt: 0°~90°		Rotate: 0°~360°
Shutter	Auto/Manual, 1~1/100000 s				
Minimum Illumination	Colour: 0.05 Lux (F2.0, AGC ON) 0 Lux with IR on				
Digital noise reduction	2D/3D DNR				
Day/Night	IR-cut filter with auto switch (ICR)				
S/N	>56dB				
IR Range	Up to 98ft (30M) IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Defog	Digital Defog				
WDR	120dB				
Video					
Video Compression	Ultra 265, H.265, H.264, MJPEG				
H.264 code profile	Baseline Profile, Main Profile				
Frame Rate	Main Stream: 8MP (3840*2160): Max. 20 fps; 5MP (2944*1656): Max. 30 fps; 4MP (2560*1440): Max. 30 fps; 2MP (1920*1080): Max. 30 fps Sub Stream: 720P (1280*720): Max. 20 fps Third Stream: 4CIF (704*576): Max. 20 fps				
Video Bit Rate	128 Kbps~16 Mbps				
OSD	Up to 4 OSDs				
Privacy Mask	Up to 4 areas				
ROI	Up to 2 areas				
Motion Detection	Up to 4 areas				
Image					
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2				
Digital noise reduction	2D/3D DNR				
Smart IR	Support				
Flip	Normal/Vertical/Horizontal/180°				
Dewarping	NA				
HLC	Supported				
BLC	Supported				
Smart					
Behavior Detection	Cross line, intrusion(based on human body detection), Motion detection, tampering alarm, audio detection				

## Network

Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS
Compatible Integration	ONVIF(Profile S, Profile T), API
Client	REVO ULTRA REMOTE MYREVOCLOUD REVO ULTRA
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
	Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+

## Interface

Network	10/100M Base-TX Ethernet
Built-in Mic	Support

## Audio

Audio Compression	G.711A,G.711U
Suppression	Supported
Sampling Rate	8KHZ

## General

Power	12 V DC±25%, PoE (IEEE802.3 af)
	Power consumption: Max 5.5W
Dimensions (L × W × H)	6.6"×2.5"×2.5" (167.3×62.9×62.7mm)
Net Weight	0.99lb (0.45kg)
Material	Metal
Working Environment	-22°F ~ 140°F (-30°C ~ +60°C), Humidity: ≤95% RH(non-condensing)
Surge Protection	2KV
Ingress Protection	IP67
Reset Button	Supported

## Dimensions

