


RU16NVR2B

Video Monitor Info:

NVR RU16NVR2B does not support a spot monitor, so its HDMI and VGA outputs are always identical.

RU16NVR2B		
	Video/Audio Input	
	IP Video Input	16 Channel
	Two-way Audio Input	1-ch, RCA
	NETWORK	
	Incoming Bandwidth	112Mbps
	Outgoing Bandwidth	96Mbps
	Remote Users	128
	Protocols	P2P, UPnP, NTP, DHCP, PPPoE
Video/Audio Output		
HDMI/VGA Output	HDMI: 4K (3840x2160)@30, 1920x1080p@60, 1920x1080p@50, 1600x1200@60, 1280x1024@60, 1280x720@60, 1024x768@60 VGA: 1920x1080p@60, 1920x1080p@50, 1280x1024@60, 1280x720@60, 1024x768@60	
Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF	
Audio Output	1-ch, RCA	
Synchronous Playback	16-ch	
Corridor Mode Screen	3/4/5/7/9/10/12/16	
Decoding		
Decoding format	Ultra 265, H.265, H.264	
Decoding Capability	1 x 4K@30, 1 x 6MP@30, 1 x 5MP@30, 2 x 4MP@30, 4 x 1080p@30, 8 x 720p@30, 16 x D1	
Hard Disk		
SATA	2 SATA interfaces	
Capacity	up to 10TB for each disk	
Smart		
VCA Detection	Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking	
VCA Search	Face search, Behavior search	
Statistical Analysis	People counting	
External Interface		
Network Interface	1 RJ-45 10M/100M/1000M self-adaptive Ethernet Interface	
USB Interface	Front panel: 1 x USB2.0, Rear panel: 1 x USB2.0	
General		
Power Supply	100 ~ 240 V AC Power Consumption: ≤ 7 W(without HDD)	
Dimensions(D × W × H)	380 mm × 315mm × 49 mm (15" × 12.4"× 1.9")	
Weight	≤1.6kg (3.53lb)	
Working Environment	-10°C ~ + 55°C (+14°F ~ +131°F), Humidity ≤ 90% RH(non-condensing)	