

8CH 2 SATA 4K Network Video Recorder

RU8NVR2AX



Key Features

- 8 Channel Input
- Support 1-ch HDMI at up to 4K (3840x2160) resolution, 1-ch VGA,
- Up to 8 Megapixels resolution recording
- Support H.265/H.264 Video Formats
- Accurate retrieval, instant playback
- 2 SATA HDD up to 16 TB
- Support Various VCA detection alarm and VCA search
- Plug & Play with up to 8 independent PoE network interfaces
- Support for P2P, UPnP, NTP, DHCP, PPPoE
- Support for mobile client access

Specifications

	RU8NVR2AX
Video and Audio	
IP Video Input	8-ch
Two-way audio Input	1-ch, RCA
Network	
Incoming bandwidth	80Mbps
Outgoing bandwidth	64Mbps
Remote connection	128
Video/Audio Output	
HDMI/VGA Output	VGA: 1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz HDMI: 4K (3840x2160) /60Hz, 4K (3840x2160) /30Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz,
Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Audio Output	1-ch, RCA
Synchronous Playback	8-ch
Decoding	
Compression	H.265/H.264
Live view/Playback	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Capability	2 x 4K@30, 4 x 4MP@30, 8 x 1080p@30
Hard Disk	
SATA	2 SATA interfaces
Capacity	up to 12TB for each disk
External Interface	
Network Interface	1 RJ-45 10M/100M self-adaptive Ethernet Interface
USB Interface	Front panel: 1 x USB2.0 Rear panel: 1 x USB3.0
Alarm in	4-CH
Alarm out	1-CH
PoE	
Interface	8 independent 100 Mbps PoE network interfaces
Max Power	Max 30W for single port Max 130W in total (15W for each)
Supported Standard	IEEE 802.3at
General	
Power Supply	100 ~ 240 VAC
Consumption (without HDD and PoE)	≤ 9 W
Working Temperature	+14°F ~ +131°F
Working Humidity	10% ~ 90%
Dimensions	380mm x 315mm x 46mm (14.95" × 12.4" × 1.81")
Weight (without HDD)	≤ 5.3 lb (2.42 Kg)

Dimensions

